

**AMENDMENTS TO THE SPECIFICATION:**

Please amend the title with the following title:

CAR-SIDE MIRROR COVER WITH LIGHT LAMP AND SIDE MIRROR BEING  
USED AS THE SAME

Please replace paragraph [0032] at page 12 with the following amended paragraph:

[0032] On the other hand, the second LED 27b is mounted on an auxiliary plate 28a, and the auxiliary plate 28a is mounted to the support 28 at the end on the side far from the vehicle substantially orthogonally to the support 28. Accordingly, the second LED 27b is mounted on the first housing section 24a so as to emit the light toward the side of the vehicle, and the auxiliary plate 28a prevents the light emitted from the second LED 27b from directing toward the second housing section 24b. The first reflector 29 is mounted to the support 28 inwardly of the vehicle. The support 28 is exposed between the first reflector 29 and the auxiliary plate 28a. The exposed portion corresponds to the partitioning section 22f described above.

Please replace paragraph [0040] at page 17 with the following amended paragraph:

[0040] As shown in the figures, the side mirror body 16 is constituted by a through hole 17a, formed on the mirror plate covering member 17, into which the side mirror lamp 23 is fitted. In this case, it is necessary to form the through hole 17a at the location where the side mirror lamp 23 and the tilting device 19 do not ~~interfered~~ interfere with each other. Therefore, in order to avoid such an interference, a plurality of columns 17b for supporting the tilting device 19 on the mirror plate covering member 17 are formed integrally with the interior of the mirror plate covering member 17, and the tilting device 19 is supported by the plurality of columns 17b. The side mirror body 16 is applied to a vehicle side mirror, which does not employ the side mirror cover.